

Features



Blower

The field proven Heavy-Duty 5.3 Positive Displacement Blower is the heart of the system. Castings are machined to strict tolerances to assure maximum efficiency that allows you to move grain a greater distance without using one or more expensive booster type systems.



Airlock

To achieve and maintain best performance, the airlock components are precision machined. The steel rotors are fitted with adjustable steel tips to allow the operator to keep the airlock working at peak performance at all times. The rotor is driven by a reversible, pressure protected, hydraulic motor.



Silencer

The high efficiency silencing system reduces noise intensity by over 50% with absolutely no reduction in machine capacity. Our unique silencing design provides greater operator comfort for years of satisfaction.



Dust Separation

Pre-Cleaner Dust Separation Tank - The heavy-duty positive displacement blower is protected from dust that is removed in the pre-cleaner tank, thereby, giving the blower years of trouble free performance.



Camlock Couplers

To achieve and maintain best performance, the airlock components are precision machined. The steel rotors are fitted with adjustable steel tips to allow the operator to keep the airlock working at peak performance at all times. The rotor is driven by a reversible, pressure protected, hydraulic motor.



Capacities

CAPACITIES †	
Soybeans	2800 - 3600 bu/hr
Wheat	3000 - 3800 bu/hr
Canola	3000 - 3700 bu/hr
Barley/Corn	3200 - 4000 bu/hr

† Capacities are based on standard truck discharge height and standard intake hose length and size, using dry clean products. Can vary with conditions.